

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 03-045906  
(43)Date of publication of application : 27. 02. 1991

(51)Int. Cl. G02B 5/30  
G02F 1/13  
G02F 1/1333

(21)Application number : 02-182555 (71)Applicant : F HOFFMANN LA ROCHE AG  
NIOPIE MOSCOW RES & PROD  
ASSOC

(22)Date of filing : 10. 07. 1990 (72)Inventor : BARNIK MIKHAIL I  
BELYAEV SERGEY V  
FUENFSCHILLING JUERG  
MALIMONENKO N V  
SCHADT MARTIN  
SCHMITT KLAUS

## (30)Priority


Priority number : 89 2562	Priority date : 10. 07. 1989	Priority country : CH
89 3948	01. 11. 1989	CH
90 1641	15. 05. 1990	CH

## (54) POLARIZER

## (57)Abstract:

PURPOSE: To make it possible to take out  $\square$ 50% of incident light in the form of polarized light by providing a polarizer with a cholesteric liquid crystal layer having a Grandjean structure and a mirror which reverses the rotating direction of circularly polarized light.

CONSTITUTION: The polarizer has the cholesteric liquid crystal layer 1 and the liquid crystals have the Grandjean structure. The molecules of the liquid crystal are oriented substantially in plane by suitable boundary conditions. The ordinary mirror 2 which constitutes an orifice plate 3 is arranged apart a specified distance in parallel with the liquid crystal layer 1. The luminous flux 5 from a monochromatic light source 4 can enter the device through the orifice. As a result, not only the sharp transmutability but the flat transmittability may be embodied by using the operation mode by the linearly polarized light and the operation mode by the circularly polarized light.



## LEGAL STATUS

[Date of request for examination]  
[Date of sending the examiner's decision  
of rejection]  
[Kind of final disposal of application  
other than the examiner's decision of  
rejection or application converted  
registration]  
[Date of final disposal for application]  
[Patent number]  
[Date of registration]  
[Number of appeal against examiner's  
decision of rejection]  
[Date of requesting appeal against  
examiner's decision of rejection]  
[Date of extinction of right]

Copyright (C) ; 1998, 2000 Japan Patent Office